



**OCTORAL**



**DISCOVER SPEED**

**OCTORAL C450 SCRATCH RESISTANT RAPID REPAIR CLEAR**

# OCTORAL C450 SCRATCH RESISTANT RAPID REPAIR CLEAR



## UNIQUE COMBINATION: FAST-DRYING AND SCRATCH RESISTANT

### OCTORAL C450 SCRATCH RESISTANT RAPID REPAIR CLEAR

- Combination of fast-drying and long-lasting protection against car washes is unique in the market
- Drying time almost halved
- Quick and easy to polish
- Suitable for spot and localised repairs
- Fast-drying under all conditions (20 °C, 40 °C and 60 °C), so saving energy

## EXPERIENCE THE CONVENIENCE AND SPEED OF WORKING

### TECHNOLOGY GIVING YOU THE EDGE

There is an exciting new addition to the assortment of clear coats from Octoral that boasts impressive features. Octoral C450 Scratch Resistant Rapid Repair Clear is a scratch resistant clear coat that dries quickly in all conditions, whether force dried at 40 °C or 60 °C or naturally at room temperature (20 °C). As a result, the process is much faster, meaning a substantial increase in productivity and significant savings in energy and costs. The end result is a high gloss surface that offers prolonged protection against the weather and increased resistance to scratching in the car wash.

### C450 SCRATCH RESISTANT RAPID REPAIR CLEAR

ART#	Icon	Icon
502116001	6	1L
502116003	3	5L

### DRYING TIMES

	HARDENER	FLASH OFF	DUST FREE	DRY TO HANDLE	DRY TO POLISH
Air dry 20 °C (68 °F)*	H23	x	20 min.	45 min.	60 min.
	H25	x	25 min.	75 min.	90 min.
Forced dry 40 °C (104 °F)*	H23	x	x	5 min.	cooling down
	H25	x	x	8 min.	cooling down
Forced dry 60 °C (140 °F)*	H23	x	x	3 min.	cooling down
	H25	x	x	5 min.	cooling down

\* Drying times stated are typical values only and may vary depending on hardener, job size, spray booth set up and ambient conditions.

### MIXING RATIO

Octoral C450 Scratch Resistant Rapid Repair Clear : HS420 hardener = 5 : 1

## SHORTER THROUGHPUT TIMES AND INCREASED PRODUCTIVITY

OCTORAL C450 SCRATCH RESISTANT FAST REPAIR CLEAR PROCESS VS. TRADITIONAL CLEAR COAT PROCESS



\* Drying times stated are typical values only and may vary depending on hardener, job size, spray booth set up and ambient conditions.

HRS 1 2 3 4 5 6 7 8 9  
 ■ PREPARATION \* ■ PRIME (+ DRYING TIME) \* ■ BASECOAT/CLEAR COAT (+ DRYING TIME) \*



### DISCOVER WHICH CLEAR COAT SUITS YOUR PROJECT BEST

For every situation a clear coat with an amazing result... discover which clear coat from the Octoral range suits your project best!

# OCTORAL

## A VALSPAR AUTOMOTIVE BRAND

Octoral is a Valspar Automotive brand. Valspar Automotive is part of the listed Valspar Corporation. Founded in 1806, this parent company is one of the world's largest coating manufacturers. Valspar Automotive manufactures and distributes Octoral car refinishes.

MORE INFO?

If you'd like to know more about Octoral or Valspar Automotive, go to [www.octoral.com](http://www.octoral.com) and [www.valsparauto.com](http://www.valsparauto.com).

### REMARKABLE IN REFINISHING

valspar AUTOMOTIVE

[www.octoral.com](http://www.octoral.com)

690147002